

C-751-16 Drum Trailer

The Drum Trailer provides a compact and secure method of drum transportation. Manufactured in strong steel sections, it incorporates manually operated hydraulic lifting of drums.

There is, as an option the facility to provide drum braking, this is particularly useful when pulling the conductor during conductor stringing operations. Trailer braking is of the overrun type and is supplied to EC Specification with auto-reverse as standard. Lights are also fitted as standard.



SPECIFICATION

Drum Weight Max:	1630kg
Drum Width Max:	1200mm
Drum Diameter Max:	2185mm
Drum Diameter Min:	900mm
Tyres:	205/75 R17.5
Towing Eye:	Standard 40mm diameter eye
Towing Height:	500mm (nominal)
Height (without Drum):	1665mm
Width:	2220mm
Length:	3302mm
Weight:	560kg
Spindle Diameter:	63.5mm
Lighting:	Stop, tail, direction, indicators c/w connectors, for light
Suspension:	Swinging arm with rubber suspension
Rear Props:	Manual slide and lock type
Adjustable Jockey Wheel:	Solid tyred Wheel
Braking:	Drum brakes to EC Specification 300 x 60 override type, auto reverse, with hand brake.
Lifting Arrangement:	Hydraulically hand pump with individual valves for each ram and locking facility

ORDERING DETAILS

Product No	Description
C-751-16	Drum Trailer - 1630kg