

## C-752 Drum Trailer

The C-752 Drum Trailer has been designed to provide safe handling of cable or conductor drums. Manufactured in strong steel sections, it incorporates manually operated hydraulic lifting of drums.

There is an optional drum braking facility, which can be used to control the conductor when undertaking conductor-stringing operations. Trailer braking is of the overrun type and is supplied to EC Specification with auto reverse as standard. Lights are also fitted as standard.



### SPECIFICATION

<b>Max Drum Weight:</b>	2400kg
<b>Max Drum Width:</b>	1365mm
<b>Min Drum Diameter:</b>	1100mm
<b>Max Drum Diameter:</b>	2550mm
<b>Towing Eye:</b>	Standard 40mm dia eye
<b>Height (without drum):</b>	1720mm
<b>Width:</b>	2300mm
<b>Length:</b>	3465mm
<b>Weight:</b>	700kg
<b>Spindle:</b>	76mm
<b>Suspension:</b>	Swinging arm with aeon suspension
<b>Braking:</b>	Drum brakes to EC Specification with hand brake
<b>Lifting Arrangement:</b>	Hydraulic pump with individual valves for each ram
<b>Tyres:</b>	215/75 R17.5

### ORDERING DETAILS

<b>Product No</b>	<b>Description</b>
C-752-F	Drum Trailer - 2400kg

### OPTIONAL EXTRAS

<b>Product No</b>	<b>Description</b>
C-752-01-F	Hydraulic Drum Braking Arrangement

For Further Information

Telephone No: +44(0) 1572 723665 • Fax No: +44 (0) 1572 756009  
E-mail: [sales@cbsproducts.com](mailto:sales@cbsproducts.com) • Website: [www.cbsproducts.com](http://www.cbsproducts.com)