

C-825 Portable Hydraulic Winching System

The CBS 825 is designed to provide a fully portable winching system, by breaking down into easily transportable modules. Ideally suited for overhead line stringing work such as ABC conductors, bare conductors or re-conductoring projects, it provides a flexible system suitable where access is restricted and ground disturbance is undesirable. The winch can be pole mounted or ground mounted using the optional frame. The C-825 Hydraulic Winch comprises of a strong lightweight pole mounting frame with securing chains and incorporates a hydraulic drive and control lever.



Drum and rope not included as standard, see optional extras.

SPECIFICATION

Capacity:	1000kg Maximum Tension (approx) Average Tension 300kg
Speed Control:	0-100 metres/min Fail-safe, bi-directional section, creep and inching facility

C-826 Hydraulic Power Pack

The C-826 Hydraulic Power Pack has an 8hp petrol engine, mounted in a tubular frame with wheels and handles. This unit is suitable for operating other equipment and tools requiring the same hydraulic output. Fitted with "Power On Demand" device, the motor delivers only when required, idling when not winching.

Length:	960mm
Width:	700mm
Height:	630mm
Weight:	90kg

ORDERING DETAILS

Product No	Description
C-825	Pole Mounted Hydraulic Winch
C-825-10	Layering Device (Manual)
C-826-08-01	Hyd Power Pack 8hp Std Flow 3000psi 15 litres/min
C-826-02-F	Hose with couplings – 5 metres long (2 off)

OPTIONAL EXTRAS

Product No	Description
C-821-02	Drum 700mm, fitted with 400 metres of 8mm diameter "Paraline" Rope.
C-821-03	Drum 700mm, fitted with 600 metres of 8mm diameter "Paraline" Rope.
C-A1-680-27	Split drum for retrieving old conductor
C-825-06	Grounding frame and anchor rods
C-825-07	Split drum (outboard type)
C-825-09	Carrying handle for Hyd Motor