

Grips for Standard Aluminium and Copper Conductors

The smooth round jaw contour provides maximum contact when used on bare ACSR, aluminium and standard copper conductors.

SPECIFICATION

Product No	Range mm	Max Load kgf	Weight kg
D-1656-20-F	5.08 - 10.16	900	1.36
D-1656-30-F	7.87 - 13.46	900	1.70
D-1656-40-F	13.46 - 18.80	1400	3.40
D-1656-50-F	18.40 - 21.83	1400	3.40
D-1656-60-F	21.83 - 24.60	1400	3.40

Hot Line Grips are available by placing "H" after model number.

The grip is placed over the conductor with a Hotline stick that when removed the latch on the grip closes stopping the grip disengaging from the conductor.

Grip for Extra High Strength Cable & Conductors

SPECIFICATION

Product No	Range mm	SWL kgf	Weight kg
D-1684-5-F	5.54 - 13.97	1200	2.83
D-1684-74-F *	5.54 - 13.97	1200	2.83

* Curved jaw version to prevent slippage when pulling.



ORDERING DETAILS

Product No	Description
D-1656-20-F	Grips 5.08 - 10.16mm
D-1656-30-F	Grips 7.87 - 13.46mm
D-1656-40-F	Grips 13.46 - 18.80mm
D-1656-50-F	Grips 18.40 - 21.83mm
D-1656-60-F	Grips 21.83 - 24.60mm



ORDERING DETAILS

Product No	Description
D-1684-5-F	Grips 5.54 - 13.97mm
D-1684-74-F	Grips 5.54 - 13.97mm