

Hydraulic Press IR P 55

Hydraulic Press of 55 tons compressive capacity, suitable for compression of joints on conductors and steel ropes for electric lines (medium and high voltage).

Excellent weight/power ratio (2.9 ton/kg), easy to operate on suspension working platforms and steel towers thanks to the specific cover fitted on the press body. Maximum hexagonal key of 44 mm allows pressing of a conductor of 31.5 mm diameter. It is fitted with control valve, pressure gauge and quick release couplings and is available in 2 versions:

Dual pipe: Fitted with a control valve, pressure gauge and quick release couplings.

Single pipe: Fitted with quick release couplings; it can be changed into DUAL mode thanks to a particular adapter.



ORDERING DETAILS

Product No	Description
G-IRP-P05502F-F	55 Ton Hyd Press
G-IRP-P055STAC-F	Die for Steel compression
G-IRP-P055STAL-F	Die for Al compression
G-IRP-P05S2574-F	Anti banana device

SPECIFICATION

Max pressing force	55 tons (550 kN) (recommended working pressure 700 bar)
Press Weight	19 kg (17 kg SINGLE pipe)
Weight/Power ratio	2.9 Ton/kg
Die Weight	1 kg
Max. hexagon	44 mm
Max. stroke	17 mm
Case Dimensions	47 x 34 x 34 cm