

Swivels and Connectors

Swivels are essential for effective pulling operations of underground cables and overhead conductors. The swivels are fitted with bearings to prevent build up of twist in the cable pulling bond. CBS swivels are precision manufactured in high-grade steel with a plated finish. The safe working loads are based on a factor of safety of 3:1.

SPECIFICATION

Product No	SWL	Dia (mm)	Length (mm)	Jaw Opening	Pin Dia mm	Weight kg
D-516	800kgf	26	105	10	8	0.26
D-565	1600kgf	34	108	15	10	0.55
D-564	3500kgf	37	135	15	12.7	0.75
D-801	4500kgf	40	142	15	14	0.85



ORDERING DETAILS

Product No	Description
D-516	Swivel 800kgf
D-565	Swivel 1600kgf
D-564	Swivel 3500kgf
D-801	Swivel 4500kgf

Fused Swivels

Fused swivels are used in applications where the pulling force must not be exceeded. The fuses are replaceable and allow the swivel to break when then maximum applied load equals the rating of the fuse.



ORDERING DETAILS

Product No	Description
D-566-01-F	Fused Swivel Body 22mm
D-566-02-F	Shear Pin 3kN 10 Pack - Blue
D-566-03-F	Shear Pin 2kN 10 Pack - Brass
D-566-04-F	Shear Pin 4kN 10 Pack - Silver
D-566-08-F	Shear Pin 8kN 10 Pack - Black

Rope Connectors

Rope Connectors provide as an effective method of jointing pulling grips



ORDERING DETAILS

Product No	Description
D-956	Rope Connector - 500kg
D-1043	Rope Connector - 1000kg
D-1169	Connector - 3500kg
D-802	Connector - 4500kg
D-1164	Connector - 6000kg

For Further Information

Telephone No: +44(0) 1572 723665 • Fax No: +44 (0) 1572 756009
 F-mail: sales@cbsproducts.com • Website: www.cbsproducts.com