

C-751 Drum Trailer

The C-751 Drum Trailer comes in three versions, and provides a compact and secure method of drum transportation. Manufactured in strong steel sections, it incorporates manually operated hydraulic lifting of drums.

There is, as an option, the facility to provide a drum braking arrangement, this is particularly useful when pulling the conductor during conductor stringing operations. Trailer braking is of the overrun type and is supplied to EC Specification with auto-reverse as standard. Lights are also fitted as standard. All versions are IVA approved.



Specification

Lighting:	Stop, tail, direction, indicators c/w connectors
Suspension:	Swinging arm with aeon suspension
Braking:	Drum Brakes to EC Specification with hand brake
Lifting Arrangement:	Hand operated hydraulic pump with individual valves for each ram
Towing Eye:	50mm diameter fitted as standard



OPTIONAL EXTRAS

Drum braking arrangement available on request

PRODUCT NO.	C-751-10	C-751-13-01	C-751-16
Drum max weight	1000kg	1300kg	1630kg
Drum max width	1050mm	1100mm	1050mm
Drum max diameter	1800mm	2000mm	2185mm
Drum min diameter	1000mm	800mm	900mm
Tyres	185 R13	195 R14 08	215/75R 16C
Length	2700mm	3172mm	3419mm
Width	1950mm	2140mm	2233mm
Height (no drum)	1350mm	1646mm	1855mm
Weight	350kg	475kg	680kg
Spindle Diameter	63mm	63.5mm	70mm