

AERIAL BUNDLE CONDUCTOR (ABC) FOR INSULATED CABLE

Non-Conductive Cable Stockings

Manufactured from a man-made, high strength parallel-stranded fibre, and having a polyethylene sheath

Non-conductive, non-corrosive and abrasive resistant

Prevents damage to other components during the pulling operation

As a support grip, long life is ensured even in hostile environments



Single Weave

Dia Range mm	Minimum Breaking Strength kg	Product No	
		Single Eye	Double Eye
10 - 20	1,120	E-677-1011	E-677-1012
20 - 30	1,680	E-677-2011	E-677-2012
30 - 40	2,240	E-677-3011	E-677-3012
40 - 50	2,688	E-677-4011	E-677-4012

Double Weave

Dia Range mm	Minimum Breaking Strength kg	Product No	
		Single Eye	Double Eye
30 - 40	4,480	E-677-3021	E-677-3022
40 - 50	5,376	E-677-4021	E-677-4022
50 - 65	7,168	E-677-5021	E-677-5022
65 - 80	7,168	E-677-6521	E-677-6522
80 - 100	7,168	E-677-8021	E-677-8022

To ensure maximum grip during pulling of cables the end of the stockings should be bound over the tail for 50mm with PVC tape.

Grip Length – 600mm

Special designs, constructions are available to customer's specifications.

