#### **G-GMP-75246 ALUMINIUM & COPPER CABLE CROPPERS**



Designed for cutting Copper & Aluminium cable (not suitable for steel or ACSR)

SPECIFICATIONS		
Max Cable Diameter	32mm	
Length	533mm	
Weight	1.5kg	

ORDER	RING INFORMATION
G-GMP-75246	32mm Cable Croppers for Aluminium and Copper

## **G-GMP-75247 CABLE CROPPERS**



Designed for cutting Copper & Aluminium cable (not suitable for steel or ACSR)

SPECIFICATIONS		
Max Cable Diameter	50mm	
Length	813mm	
Weight 4kg		

ORDERING INFORMATION		
G-GMP-75247	50mm Cable Croppers for Aluminium and Copper	

## **D-805 HYDRAULIC CUTTERS**



Hand operated hydraulic cutters, designed to increase speed and reduce effort of cutting conductors and cables whilst providing a superior finish.

Models D-805-04-F & D-805-05-F are two-speed for faster operation.

ORDERING INFORMATION		
D-805-025-F	25mm Hydraulic Cutters	
D-805-04-F	45mm Hydraulic Cutters	
D-805-05-F	50mm Hydraulic Cutters	
D-805-085-F 85mm Hydraulic Cutters		

SPECIFICATIONS	D-805-025	D-805-04-F	D-805-05-F	D-805-085
Cu/Al Cable	25	45	50	85
Cu/ACSR Conductor	25	45	-	-
Weight	3.2kg	5.8kg	4.4kg	6.6kg



Designed for cutting ACSR Conductors up to 23mm diameter.

	SPECIFICATIONS	
Length	457mm	
Weight	1.81kg	

ORDERING	3 INFORMATION
G-GMP-75248	Heavy Duty Ratchet Cutter

# **G-GMP-75249 ACSR QUICK RELEASE RATCHET CUTTERS**



Quick action Ratchet Cutters designed for use on Copper & Aluminium cables. (Not for Steel)

	SPECIFICATIONS	
Length	457mm	
Weight	1.9kg	

ORDERING INFORMATION		
G-GMP-75249	Quick Release Heavy Duty Ratchet Cutter	

## **G-GMP-75247 CABLE CROPPERS**



Designed for cutting Copper & Aluminium Cables (not suitable for steel or ACSR).

	SPECIFICATIONS	
Length	220mm	
Weight	0.28kg	

ORDER	ING INFORMATION
G-GMP-15304	Cable Croppers

#### **D-557-4-F SPANOMETER CABLE MEASURING MACHINE**



This machine has been designed to measure lengths of overhead cables. The unit is hung on the cable and a vertically movable pulley is used to clamp the measuring wheel to the cable. A shackle is provided to enable the machine to be pulled along. A mechanical counter then displays the length/distance that the machine has moved. Its primary use is for positioning of spacers on overhead power lines. Can accommodate cable sizes between 8-43mm diameters.

ORDERING	INFORMATION

D-557-4-F Overhead Cable/Rope Measuring Device

#### **D-914 RIDGID ACSR CABLE TRIMMER**



Fast, accurate cable splice preparation. The bushing holder, cutter and handy carrying case are sold as one unit. Case contains storage sockets for 11 bushings.

	SPECIFICATIONS	
Weight	2.8kg	

# D-914-RIDGID-87-F ACSR Cable Trimmer D-914-RIDGID-87-01-F Ridgid Cutter wheel No.87

#### **D-914 RIDGID BUSHINGS**



Multiple bushing types are available to fit the RIDGID ACSR tool.

ORDERING INFORMATION			
D-914-RIDGID-HORSE	70mm <sup>2</sup>		
D-914-RIDGID-LYNX	175mm <sup>2</sup>		
D-914-RIDGID-ZEBRA	400mm <sup>2</sup>		
D-914-RIDGID-CROW	361.6mm <sup>2</sup>		
D-914-RIDGID-OSLOW	325mm <sup>2</sup>		
D-914-RIDGID-WOLF	150mm <sup>2</sup>		
D-914-RIDGID-LONDON	780mm <sup>2</sup>		
D-914-RIDGID-MATTHEW	56.3mm <sup>2</sup>		

sales@cbsproducts.com +44 (0)1572 723 665

## **D-840 YALE ERGO LEVER HOIST**



Little effort is required to operate this high quality aluminium ratchet lever hoist. Offering faultless chain movement due to the guide being cast into the body and free chaining.

ORDERING INFORMATION	D-840-07-ERGO	D-840-15-ERGO	D-840-30-ERGO	D-840-60-ERGO
Capacity	750kg	1,500kg	3,000kg	6,000kg
Lift	1500mm	1500mm	1500mm	1500mm
Chain Dims	5.6 x 17.1mm	7.1 x 21mm	10 x 28mm	10 x 28mm
Weight	6.6kg	9.5kg	16.8kg	28.6kg

## **D-840 YALE HANDY LEVER HOIST**



Smallest and lightest in the Yale range, making it suitable for a multitude of applications. Its size makes it easy to use, and ideal for tight working environments. The free chaining device allows for fast load attachment.

ORDERING INFORMATION	D-840-02-F	D-840-05-F
Capacity	250kg	500kg
Lift	1500mm	1500mm
Chain Dims	4 x 12mm	4 x 12mm
Weight	2.2kg	2.8kg



The universal PT series lever hoists feature pressed steel housings and are extremely lightweight. The PT series are ideal for applications where economy is a decisive factor.

ORDERING INFORMATION	D-840-07-F	D-840-15-F	D-840-30-F	D-840-60-F
Capacity	800kg	1,600kg	3,200kg	6,300kg
Lift	1500mm	1500mm	1500mm	1500mm
Chain Dims	5.6 x 17.1mm	7.1 x 21.2mm	9 x 27.2	9 x 27.2
Weight	5.5kg	9.6kg	16kg	31kg

## **D-1143 YALE UNOPLUS LEVER HOIST**



These versatile ratchet lever hoists are compact, lightweight and feature stamped steel construction. The units represent superb economy and ship complete with free chaining device for fast load attachment.

ORDERING INFORMATION	D-1143-07-F	D-1143-15-F	D-1143-30-F	D-1143-60-F
Capacity	750kg	1,500kg	3,000kg	6,000kg
Lift	1500mm	1500mm	1500mm	1500mm
Chain Dims	6 x 18mm	8 x 24mm	10 x 30mm	10 x 30mm
Weight	7.2kg	12.5kg	21.5kg	32kg

## **D-785 MINI RATCHET PULLER**



Specially designed and developed to meet the specific needs of linesmen for tensioning applications. The units are compact and lightweight, easy to operate in any position and feature a ratchet and automatic brake.

ORDERING INFORMATION		
D-785-10-F	1,000kg Ratchet Puller	
D-785-15-F	1,500kg Ratchet Puller	

SPECIFICATIONS	D-785-10-F	D-785-15-F
Capacity	1,000kgf	1,500kgf
Wire Diameter	5	6.3
Wire No.	2	2
Min Length	410mm	450mm
Max Length	1210mm	1220mm
Weight	3.15kg	4.3kg

## **D-785 INSULATED WEB STRAP MINI RATCHET PULLER**



	D-785-10-WS-F	D-785-15-WS-F
Capacity	1,000kgf	1,500kgf
Strap Size	2 x 33mm	2 x 40mm
Min Length	440mm	470mm
Max Length	1940mm	1970mm
Weight	3.3kg	4.6kg

ORDERING INFORMATION		
D-785-10-WS-F	1,000kg Ratchet Puller	
D-785-15-WS-F	1,500kg Ratchet Puller	

## **TENSIONING PULLERS**

Designed to be compact and lightweight for tensioning applications (not for lifting).

## D-786 RATCHET PULLERS - RICKY 2 & 3

SPECIFICATIONS	D-786-07-2-F Ricky 2	D-786-15-F Ricky 3
Capacity	750kg	1,500kg
Chain Diameter	5mm	5mm
Min Length	300mm	350mm
Max Length	1,800mm	1,850mm
Lever Length	230mm	230mm
Pull Length	1.5m	1.5m
Weight	4kg	5kg



Ricky 2



Ricky 3

## **D-803 MINI RATCHET PULLERS**



SPECIFICATIONS	D-803-F	D-803-13-F	D-803-18-F	D-803-22-F	D-803-25-F
Capacity	750kg	750kg	750kg	750kg	750kg
Chain Diameter	5mm	5mm	5mm	5mm	5mm
Min Length	330mm	330mm	330mm	330mm	330mm
Max Length	1,100mm	1,300mm	1,800mm	2,200mm	2,500mm
Lever Length	400mm	400mm	400mm	400mm	400mm
Pull Length	1.1m	1.3m	1.8m	2.2m	2.5m
Weight	3.8kg	4.2kg	4.4kg	4.6kg	4.8kg

#### **D-477 TIRFOR ROPE HOIST**



Ideal lifting and pulling device where long strokes are required. 20m of rope supplied as standard, longer ropes available on request.

ORDERING INFORMATION			
D-477-08T-F	800kg Tirfor Cable Puller		
D-477-16T-F	1,600kg Tirfor Cable Puller		
D-477-32T-F	3,200kg Tirfor Cable Puller		

SPECIFICATIONS	D-477-08T-F	D-477-16T-F	D-477-32T-F
Lifting Capacity	800kg	1,600kg	3,200kg
Pulling Capacity	1,250kgf	2,500kgf	5,000kgf
Rope Diameter	8.4mm	11.5mm	<b>1</b> 6mm

## **D-477 YALETRAC CABLE PULLERS**



Yaletrac cable pullers feature a lightweight, compact, high strength aluminium housing, smooth contour design with a large, flat bottom surface for increased stability in horizontal and vertical working positions.

ORDERING INFORMATION				
D-477-08Y-F	800kg Yaletrac Cable Puller			
D-477-16Y-F	1,600kg Yaletrac Cable Puller			
D-477-32Y-F	3,200kg Yaletrac Cable Puller			

SPECIFICATIONS	D-477-08Y-F	D-477-16Y-F	D-477-32Y-F
Capacity	800kg	1,600kg	3,200kg
Rope Diameter	8.4mm	11.5mm	16mm

## **D-732 ANALOG DYNAMOMETER**



ORDERING INFORMATION			
D-732-05-F	5kN Dynamometer		
D-732-10-F	10kN Dynamometer		
D-732-20-F	20kN Dynamometer		
D-732-30-F	30kN Dynamometer		
D-732-50-F	50kN Dynamometer		

SPECIFICATIONS	5kN	10kN	20kN	30kN	50kN
Length	110mm	135mm	135mm	150mm	260mm
Diameter	65mm	65mm	65mm	80mm	95mm
Eye Diameter	11mm	16mm	16mm	28mm	28mm
Weight	0.7kg	0.8kg	1.2kg	2.3kg	3.5kg

## **D-731 DIGITAL LOAD INDICATORS**



The new digital load indicators are compact measuring devices for the weighing of loads. On account of their flexibility, these load indicators are suitable for a multitude of applications. Whether used as a conventional crane weighing machine or to

measure forces, it is the economical choice for various applications. Simple and straight forward to use! The load indicators have an LCD display.

ORDERING INFORMATION		
D-731-01-F	1,000kg Digital Dynamometer	
D-731-025-F	2,500kg Digital Dynamometer	
D-731-05-F	5,000kg Digital Dynamometer	

SPECIFICATIONS	D-731-01-F	D-731-025-F	D-731-05-F
Range	0-1,000kg	0-2,500kg	0-5,000kg
Accuracy %	0.2	0.2	0.2
Resolution Step	1kg	1kg	1kg

## **D-257 DOUBLE PODGER RATCHET**



Ratchet facility in both directions, two sizes per wrench.

ORDERING	Flat Size	Bolt Size
D-251-1014-F	10x14mm	M6xM8
D-257-1113-F	10x13mm	$^{1}/_{4} \times ^{5}/_{16}$
D-257-1317-F	13x17mm	M8xM10
D-257-1719-F	17x19mm	M10xM12
D-257-1921-F	19x21mm	$^{7}/_{16} \times ^{1}/_{2}$

ORDERING	Flat Size	Bolt Size
D-257-1924-F	19x24mm	M12xM16
D-257-2126-F	21x26mm	$^{1}/_{2} \times ^{5}/_{8}$
D-257-2430-F	24x30mm	M16xM20
D-257-2632-F	26x32mm	<sup>5</sup> / <sub>8</sub> x M22
D-257-3032-F	30x32mm	M20xM22
D-257-3235-F	32x35mm	$^{3}/_{4} \times ^{7}/_{8}$
D-257-3236-F	32x36mm	M22xM24
D-257-3541-F	35x41mm	<sup>7</sup> / <sub>8</sub> x 1
D-257-3641-F	36x41mm	M24xM27
D-257-4146-F	41x46mm	M27xM30

# **D-258 DOUBLE RATCHET SPANNER**



A universal tool, ratchet facility in both directions, two sizes per wrench. Sizes from  $13 \times 17$  to  $30 \times 32$ mm A/F.

ORDERING	Flat Size	Bolt Size
D-258-1317-F	13x17mm	M8xM10
D-258-1719-F	17x19mm	M10xM12
D-258-1921-F	19x21mm	$^{7}/_{16} \times ^{1}/_{2}$
D-258-2126-F	21x26mm	$^{1}/_{2}$ x $^{5}/_{8}$
D-258-2224-F	22x24mm	M14xM16
D-258-2427-F	24x27mm	M16xM18
D-258-2430-F	24x30mm	M16xM20
D-258-3032-F	30x32mm	M20xM22

## **UB20 BLOWER/EXHAUSTER**



SPECIFICATIONS	
Fan Diameter	200mm
Dimensions	355 x 305 x 330mm
Weight	8kg
Noise	74dB

	ORDERING INFORMATION	
D-ED9002-F	12V DC Blower	
D-ED8002-F	240V AC Blower	
D-ED6002-F	110V AC Blower	

Ramfan combines high performance turbofan design with high strength polymers to create a line of rugged, portable turbo blowers. The line is ideal for general use, confined space, hazardous ventilation and delivers the highest airflow in their class. The double-wall, polyethylene case is lightweight, corrosion and chemical resistant and handles the bumps and falls of any jobsite.

- Powerful, compact size and lightweight.
- High pressure axial blower with 9 blade impeller.
- ◆ Corrosion proof, dent resistant and virtually indestructible.
- ♦ Double-walled UV resistant polyethylene house.

- Ultra quiet operation.
- Thermal switch provides overheat protection.
- ◆ AC-15 ft cord c/w power switch, IP65 rain tested switch enclosure.
- ♦ DC-15 ft cord c/w battery clips.

SPECIFICATIONS	D-ED9002-F	D-ED8002-F	D-ED6002-F
Free Air	862cfm/hr	819cfm/hr	819cfm/hr
4.6m 1x 90° Turn	695cfm/hr	659cfm/hr	659cfm/hr
4.6m 2x 90° Turn	586cfm/hr	558cfm/hr	558cfm/hr
Power	12V DC 11.5A	240V AC 1.2A	110V AC 1.2A

<sup>\*\*</sup>Also requires D-BPV-12CE-F Battery pack to operate.

#### **QUICK-COUPLE REVERSIBLE CANISTER**



Detachable in seconds, the Quick-Couple canister with attached duct conveniently reverses from discharge to suction, making use and storage easier while protecting duct from rips and tears.

ORDERING INFORMATION		
D-ED6015-F 4.6m duct 110V 50Hz Blower		
D-ED6025-F	7.6m duct 110V 50Hz Blower	
D-ED8015-F	4.6m duct 220V 50Hz Blower	
D-ED8025-F	7.6m duct 220V 50Hz Blower	
D-ED9015-F**	4.6m duct 12V DC Blower	
D-ED9025-F**	7.6m duct 12V DC Blower	

<sup>\*\*</sup>Also requires D-BPV-12CE-F Battery pack to operate

	4.6m CANISTER	7.6m CANISTER
Dimensions	356 x 305 x 800mm	356 x 305 x 1050mm

#### **UB20 MANHOLE ENTRY DEVICE**



ORDERING INFORMATION			
D-ED6015-MED-F	110V/50Hz Blower and 4.6m/1.5m Duct		
D-ED8015-MED-F	220V/50Hz Blower and 4.6m/1.5m Duct		
D-ED9015-MED-F**	12V DC Blower and 4.6m/1.5m Duct		

<sup>\*\*</sup>Also requires D-BPV-12CE-F Battery pack to operate

The MED allows workers to enter and exit small man-size openings while maintaining continuous ventilation. Without such a device, duct fills the manhole opening, preventing rapid entry and exit. Tightly integrated into the UB line of confined space ventilation equipment, the MED is quick to assemble and the new swivelling elbow makes duct alignment easy.

Changing its cross section from circular to elliptical and back to circular minimises loss and optimises airflow into a confined space, while providing adequate room for a worker to enter and exit unimpeded. The rugged polyurethane construction endures heavy, negligent use and will last for years.

#### **UB20 12V DC WITH BATTERY & CHARGER**



ORDERING INFORMATION			
D-ED9015-BATCE-F	UB20 12V DC 4.6m Blower Kit		
D-ED9025-BATCE-F	UB20 12V DC 7.6m Blower Kit		

The long life battery pack features high-low control. Pulse width modulation extends the battery up to 10 hours in the low setting, yet gives a full 2.5 hours on high. Can be used with vehicle batteries with optional connector. Built-in charger allows you to fully recharge the battery in 12 hours.

Purge the area on high for 10 minutes, then switch to low speed (low noise as well) and maintain fresh air for the whole work shift. Ideal for construction job sites to eliminate noisy petrol powered blowers.

#### **UB20 IN-LINE HEATING SYSTEM**



	D-HA02-F	D-HA03-F
Power	110V AC 50Hz	240V AC 50Hz
Output	70k BTU	70k BTU
Weight	13.5kg	13.5kg

The in-line heating system with its propane-fired heat exchanger provides safe, warm breathing air in cold conditions.

- For tent/shelter or confined space heating.
- Remote thermostat included.
- Up to 10 hours continuous operation with standard propane gas cylinder.
- Heater attaches quickly and easily to UB20 blower.
- Includes propane regulator and connection assembly.
- Easy access top-mounted heater control panel.

ORDERING INFORMATION		
D-HA02-F	110V AC 50Hz Heater	
D-HA03-F	240V AC 50Hz Heater	



#### **D-161 A STYLE JOINTER'S UTILITENT**



Designed to protect workers from the elements, these brightly coloured tents are easily seen by oncoming traffic. The tents are made from a durable, water repellent nylon/polyester, with adjustable rod ends for side wall tension, zipped door, vent windows and tie down loops on all corners and can pop up or down in a matter of seconds, requiring no assembly.

**A-Style:** Includes two screen windows with roll up flaps, three tie down cords through the hub, ground flaps, single zippered front door, exterior roof line loops for tie down.

ORDERING INFORMATION	D-161-00-F	D-161-01-1-F
Dimensions	1.8 x 1.8 x 1.8m	2.4 x 2.4 x 2.0m
Weight	9.1kg	14.1kg

# **D-161 D STYLE JOINTER'S UTILITENT**



**D-Style:** Includes two screen windows with roll up flaps, three tie down cords through the hub, ground flaps, heavy duty frame, wide open front, snap and loops with interconnectable flaps (connect 2 tents together), ventilation hose entry sleeve, interior and exterior roof line loops for tie down.

ORDERING INFORMATION	D-161-02-F	D-161-03-F
Dimensions	1.8 x 1.8 x 1.8m	2.4 x 2.4 x 2.0m
Weight	9.5kg	14.5kg